

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

Claim 1 (currently amended). An apparatus for use in a building automation system, the building automation system including one or more devices that are operable to generate control outputs based on set point information and process value information from one or more sensors, the building automation system further including one or more actuators operable to perform an operation responsive to at least some of the control outputs, the apparatus comprising:

at least one microelectromechanical (MEMs) sensor device operable to generate a process value;

a processing circuit configured to ~~convert the process value to cause~~ cause an output digital signal ~~and to cause the output digital signal~~ to be communicated to another element of the building automation system; and

wherein the at least one MEMs sensor device and the processing circuit are integrated onto a first substrate; and

wherein the processing circuit is further configured to generate the output digital signal including a first control output based on at least one set point and the process value obtained from the at least one MEMs sensor device, ~~and wherein the output digital signal is representative of the first control output.~~

Claim 2 (previously presented). The apparatus of claim 1 wherein the processing circuit includes a microelectronics A/D converter, the microelectronics A/D converter operable to receive the process value from the at least one MEMs sensor device and generate a digital sensor signal therefrom.

Claims 3-4 (canceled).

Claim 5 (original). The apparatus of claim 1 wherein the at least one MEMs sensor device includes a plurality of MEMs sensor devices.

Claim 6 (original). The apparatus of claim 1 further comprising a battery secured to the first substrate.

Claim 7 (original). The apparatus of claim 1 wherein the first substrate is a semiconductor substrate.

Claim 8 (original). The apparatus of claim 6 wherein the battery further comprises a lithium ion battery layer.

Claim 9 (original). The apparatus of claim 8 further comprising a power management circuit operably coupled to the lithium ion battery layer.

Claim 10 (original). The apparatus of claim 8 further comprising a second substrate, and wherein the lithium ion battery layer is disposed between the first substrate and the second substrate.

Claim 11 (previously presented). The apparatus of claim 1 further comprising an RF communication circuit operably coupled to the processing circuit, the RF communication circuit operably connected to provide the output digital signal to the other element of the building automation system.

Claim 12 (original). The apparatus of claim 1 further comprising an EEPROM operably coupled to the processing circuit.

Claims 13-20 (canceled).

Claim 21 (currently amended). An apparatus for use in a building automation system, the building automation system including one or more devices that are operable to generate a control output based on set point information and process value information from one or more sensors, the apparatus comprising:

at least one microelectromechanical (MEMs) sensor device operable to generate a process value;

a processing circuit operably connected to the at least one MEMs sensor device to receive the process value therefrom, the processing circuit configured to convert the process value to an output digital signal configured to be communicated to another element of the building automation system;

a battery operably connected to provide power to at least the processing circuit; and

wherein the at least one MEMs sensor device and the processing circuit are integrated onto a first substrate, and wherein the battery is secured between ~~to~~ the first substrate and a second substrate of the apparatus.

Claim 22 (currently amended). The apparatus of claim 21 wherein the second ~~first~~-substrate is a semiconductor substrate.

Claim 23 (previously presented). The apparatus of claim ~~[[22 ]]~~21 wherein the battery further comprises a lithium ion battery layer.

Claim 24 (previously presented). The apparatus of claim 23 further comprising a power management circuit operably coupled to the lithium ion battery layer.

Claim 25 (canceled).

Claim 26 (currently amended). An apparatus for use in a building automation system, the building automation system including one or more devices that are operable to generate a control output based on set point information and process value information from one or more sensors, the apparatus comprising:

at least one microelectromechanical (MEMs) sensor device operable to generate a process value;

a processing circuit operably connected to the at least one MEMs sensor device to receive the process value therefrom, the processing circuit configured to convert the process value to an output digital signal configured to be communicated to another element of the building automation system;

a programmable non-volatile memory operably coupled to the processing circuit and supported by the first substrate, wherein the programmable non-volatile memory stores configuration information relating to the apparatus; and

wherein the at least one MEMs sensor device and the processing circuit are integrated onto a first substrate.

Claim 27 (previously presented). The apparatus of claim 26, wherein the programmable non-volatile memory comprises an EEPROM configured to store information generated by an external device selecting less than all of the available functions of the apparatus to be enabled.

Claim 28 (canceled).

Claim 29 (previously presented). The apparatus of claim 28, wherein the configuration information includes identification information for the apparatus.

Claim 30 (previously presented). The apparatus of claim 29, wherein the configuration information includes a network address corresponding to the apparatus.

Claim 31 (previously presented). The apparatus of claim 28, wherein the configuration information includes function enabling information, the function enabling information identifying as enabled less than all of the possible sensing functions available to be enabled on the sensor.

Claim 32 (previously presented). The apparatus of claim 28, wherein the configuration information includes system RF communication parameters.

Claim 33 (previously presented). The apparatus of claim 27, wherein the EEPROM is further operable to store configuration information relating to the apparatus.

Claim 34 (previously presented). The apparatus of claim 33, wherein the configuration information includes identification information for the apparatus.

Claim 35 (previously presented). The apparatus of claim 33, wherein the configuration

information includes function enabling information, the function enabling information identifying as enabled less than all of the possible sensing functions available to be enabled on the sensor.

Claim 36 (previously presented). The apparatus of claim 27, wherein the EEPROM is integrated on to the first substrate.